

# MATERIAL SAFETY DATA SHEET

DATE PRINTED: 3/21/2002

PAGE 1  
MSDS NO. ACSA30.2

## SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

MANUFACTURERS NAME  
W.M. BARR & COMPANY, INC.

ADDRESS  
2105 Channel Avenue  
Memphis, TN 38113 USA

EMERGENCY TELEPHONE #1  
901-775-0100

EMERGENCY CONTACT  
W.M. Barr Technical Services

EMERGENCY INFORMATION  
See Section 5 for additional Emergency Information

INVENTORY ITEM #  
CHEMICAL FORMULA  
ACSA30.2

PRODUCT NAME  
CITRISTRIP AEROSOL PAINT AND VARNISH REMOVER

REVISED BY  
W.M. Barr Technical Services

REVISION DATE  
3/07/2002

## SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

### CARCINOGENICITY

SUBSTANCE DESCRIPTION	PERCENT	CAS#	NTP	ACGIH	OSHA	IARC
CITRUS TERPENES	35- 40	5989-27-5	N	N	N	N
1-METHYL-2-PYRROLIDONE	60- 65	872-50-4	N	N	N	N
DIMETHYL ETHER	20- 25	115-10-6	N	N	N	N

## SECTION 3. REGULATORY INFORMATION

### EXPOSURE LIMITS/REGULATORY INFORMATION

SUBSTANCE DESCRIPTION	REG.AGCY	U/M	TWA	STEL	CEIL	SKIN	PEL
CITRUS TERPENES	ACGIH	PPM	N/E	N/E	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	N/E
1-METHYL-2-PYRROLIDONE	ACGIH	PPM	N/E	N/E	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	N/E

RECOMMENDED EXPOSURE LIMIT: 100 PPM TWA, AS PROVIDED BY SUPPLIER.

DIMETHYL ETHER	ACGIH	PPM	N/E	N/E	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	N/E

### ADDITIONAL REGULATORY INFO

The time weighted average (TWA) value described herein is a threshold limit value (TLV) as established by ACGIH. The permissible exposure limit (PEL) is a value established by OSHA.

### CALIFORNIA (PROPOSITION #65)

WARNING: Using this product will expose you to chemicals which are known to cause birth defects or other reproductive harm.

### SEC. 313 SUPPLIER NOTIFICATION

The following information must be included in all MSDS that are copied and distributed for this material.

This product contains no chemicals subject to the reporting requirements of SARA III: Section 313.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 3/21/2002

PAGE 2  
MSDS NO. ACSA30.2

-----  
SECTION 3. REGULATORY INFORMATION  
(CONTINUED)  
-----

SUBSTANCE DESCRIPTION	PERCENT BY WEIGHT (UPPER LIMIT)	CAS#
1-METHYL-2-PYRROLIDONE	65	872-50-4

**CLEAN AIR ACT**

This formula contains no known ozone depleting chemicals.

**HAZARD COMMUNICATION STANDARD**

This document is prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200). This MSDS contains thirteen (13) sections.

\*\*\*\*\*

The following effects and/or symptoms are not expected to be experienced by persons who use this product properly and according to ALL instructions, precautions, and warnings; however, should the product user experience ANY questionable effects or symptoms, the product user should immediately seek medical attention.

-----  
SECTION 4. HAZARDS IDENTIFICATION  
-----

**INHALATION ACUTE EXPOSURE EFFECTS**

May cause dizziness; headache; irritation of the respiratory tract and mucous membranes; nausea; giddiness; mental confusion. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

**SKIN CONTACT ACUTE EXPOSURE EFFECTS**

May cause irritation; itching; burning; redness; inflammation; cracking. May cause dermatitis in people with sensitive skin.

**EYE CONTACT ACUTE EXPOSURE EFFECTS**

May cause irritation; redness; tearing; burns; conjunctivitis of eyes; stinging of eyes and lids.

**INGESTION ACUTE EXPOSURE EFFECTS**

Harmful or fatal if swallowed. May cause nausea; vomiting; gastrointestinal irritation; and diarrhea.

**CHRONIC EXPOSURE EFFECTS**

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Repeated exposure may cause dermatitis. May cause skin irritation; photosensitivity.

**MEDICAL CONDITIONS AGGRAVATED**

None known.

**PRIMARY ROUTE OF EXPOSURE**

Inhalation, ingestion, and dermal.

-----  
SECTION 5. FIRST AID MEASURES  
-----

**INHALATION**

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

**SKIN CONTACT**

Wash with soap and water. Get medical attention.

# MATERIAL SAFETY DATA SHEET

DATE PRINTED: 3/21/2002

PAGE 3  
MSDS NO. ACSA30.2

## SECTION 5. FIRST AID MEASURES (CONTINUED)

### EYE CONTACT

Immediately flush with water, remove any contact lens, flush with water for at least 15 minutes. Get medical attention.

### INGESTION

DO NOT induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.

### NOTE TO PHYSICIAN

This formula is registered with POISINDEX.  
Call your local poison control center for further information.

## SECTION 6. FIRE FIGHTING MEASURES

HAZARD RATING SOURCE	HMIS	NFPA
HEALTH	2	2
FLAMMABILITY	4	4
REACTIVITY	0	0
OTHER	G	NA

### FLASH METHOD

FLAME EXTENSION

### FLASH POINT

N/E F N/E C

### LOWER EXPLOSION LIMIT

N/E

### GENERAL COMMENTS

Aerosol Flammability Classification according to ASTM D-3065-77 and FHSA 1500.45.  
CPSC FLAMMABILITY: Extremely Flammable Aerosol

### EXTINGUISHING METHOD

Use carbon dioxide, dry powder, or foam.

### FIRE FIGHTING PROCEDURES

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Stay away from heads of containers that have been exposed to intense heat or flame.

### FIRE AND EXPLOSION HAZARDS

Contents under pressure. Do not puncture, incinerate or store above 120 degrees F. Exposure to heat or prolonged exposure to sun may cause bursting.

## SECTION 7. ACCIDENTAL RELEASE MEASURES

### CLEAN-UP

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. SMALL SPILLS: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. LARGE SPILLS: dike far ahead of spill for later disposal.

For transportation related spills contact Chemtrec at 1-800-424-9300 for emergency assistance.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 3/21/2002

PAGE 4  
MSDS NO. ACSA30.2

-----  
SECTION 7. ACCIDENTAL RELEASE MEASURES  
(CONTINUED)  
-----

**WASTE DISPOSAL**

Dispose in accordance with applicable local, state and federal regulations.

-----  
SECTION 8. HANDLING AND STORAGE  
-----

**STORAGE**

Replace overcap on container after each use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

**HANDLING**

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

-----  
SECTION 9. TRANSPORT INFORMATION  
-----

**TRANSPORTATION**

For D.O.T. information, contact W.M. Barr Technical Services Department.

-----  
SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

**VENTILATION PROTECTION**

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is inadequate. Leave area immediately.

**RESPIRATORY PROTECTION**

For OSHA controlled work place and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

**SKIN PROTECTION**

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

**EYE PROTECTION**

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

**OTHER PROTECTION**

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 3/21/2002

PAGE 5  
MSDS NO. ACSA30.2

-----  
SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES  
-----

**VOLATILE %**

96  
BY WEIGHT

**BOILING POINT**

GT 347.00 F 175.00 C BOILING RANGE: 347 F - 396 F

**VAPOR DENSITY (Air = 1.0)**

HEAVIER THAN AIR

**EVAPORATION RATE**

SLOWER THAN ETHER

**BULK DENSITY**

8.029  
LBS/GAL AT 75 DEGREES F

**pH FACTOR**

N/E

**PHOTOCHEMICALLY REACTIVE**

YES

**MAX V.O.C.**

96.6% by weight

**MAX VAPOR PRESSURE**

<1mm Hg at 20 degrees C

-----  
SECTION 12. STABILITY AND REACTIVITY  
-----

**INCOMPATIBILITIES**

Incompatible with strong oxidizing agents; reducing agents;  
halogens; peroxides; vinyl chloride; and iodine chloride.

**DECOMPOSITION**

Thermal decomposition may produce carbon monoxide; carbon dioxide;  
oxides of nitrogen; acrid smoke; fumes.

**POLYMERIZATION**

Will not occur.

**STABILITY**

Stable.

-----  
SECTION 13. ADDITIONAL INFORMATION  
-----

**IMPORTANT NOTE**

The information contained herein is presented in good faith and  
believed to be accurate as of the effective date shown above. This  
information is furnished without warranty of any kind. Employers  
should use this information only as a supplement to other  
information gathered by them and must make independent determination  
of suitability and completeness of information from all sources to  
assure proper use of these materials and the safety and health of  
employees. Any use of this data and information must be determined  
by the user to be in accordance with applicable federal, state and  
local laws and regulations.

**LEGEND:**

PPM = parts per million  
MG/M3 = milligrams per cubic meter  
N/E or NE = none established  
GT = greater than

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 3/21/2002

PAGE 6  
MSDS NO. ACSA30.2

-----  
SECTION 13. ADDITIONAL INFORMATION  
(CONTINUED)  
-----

N/A or NA = not applicable  
TCC = tag closed cup  
TOC = tag open cup  
PMCC = Pensky-Martens closed cup  
IDLH = Immediately Dangerous to Life and Health

\*\*\*END OF MSDS\*\*\*